

Mapped, edited, and published by the Geological Survey Kentucky area mapped in cooperation with Kentucky Geological Survey Topography in West Virginia by photogrammetric methods from

aerial photographs taken 1957. Field checked 1963

from aerial photographs:

Revised 1963

Topography in Kentucky by photogrammetric methods from aerial photographs taken 1951 Field checked 1954

UTM GRID AND 1975 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

CONTOUR INTERVAL 40 FEET NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION US Route State Route

NAUGATUCK, W. VA.-KY.

SE/4 NAUGATUCK 15 QUADRANGLE

QUADRANGLE LOCALL N 1963

1:60,000 (black and white) 1959 1:80,000 (black and white) 1975 Photointerpretation and field check 1977 This report is preliminary and has not been reviewed for conformity with U. S. Geological Survey editorial standards. Data on location of strip mines in part from: Alvord, Donald C., 1971, Geologic maps of parts of the Naugatuck and Delbarton quadrangles, eastern Kentucky: U. S. Geological Survey

Geologic Quadrangle Map GQ-879, scale 1:24,000.

Landslides and related features interpreted

ACTIVE OR RECENTLY ACTIVE LANDSLIDE Complex landslide composed of earthflow, debris slide, earth and rock slump. Identified from historical records, and from scars, debris and other field evidence. Ground extremely unstable; sliding accelerated by excavation, loading and changes in drainage conditions. May include areas with several active slides too small to be shown separately. Questioned where doubtful.

OLD LANDSLIDE Area of extensive hummocky ground caused by earthflow and earth and rock slump. Lacks clear evidence of active sliding. Relatively stable in natural, undisturbed state, generally not affected by small structures properly sited in areas away from the edge of the toe; can be reactivated by extensive, rapid excavation, loading, and changes in ground water and surface water conditions. Area of old landslide probably includes recent ones not identified from field evidence or otherwise documented. Upslope boundary of landslide generally defined by modified scarp, but downslope (toe) may be gradational and not well defined. Questioned where doubtful.

COMBINATION LANDSLIDE Area of recent and old slides in which individual slides are not identified.

COLLUVIAL SLOPE Valley wall along major streams with slope as steep as 40° (85%); stony, clayey silt soil up to 50 ft. (15 m) thick; commonly buttressed by a terrace or bench at the toe of the slope; very susceptible to sliding by cutting of toe area, removal of terrace or bench, and overloading; slide commonly activated without apparent cause. LANDSLIDES AND RELATED FEATURES

OF THE NAUGATUCK, W. VA. - KY. QUADRANGLE William F. Outerbridge 1982 U.S. Geological Survey OPEN FILE MAP 82-51 (G-14)

COLLUVIAL SLOPES WITH LANDSLIDES Landslides too small or obscure to map individually.

AREAS SUSCEPTIBLE TO DEBRIS FLOWS AND DEBRIS **AVALANCHES** Primarily shallow, narrow ravines and chutes with accumulation of stony colluvium generally 10 ft. (3 m) or less in thickness; susceptible to rapid movement during intense rainfall. Most ravines and chutes designated show evidence of former debris flows and avalanches. Symbol & designates historical debris flow or debris avalanche.

AREAS SUSCEPTIBLE TO ROCKFALL Steep, locally vertical, natural and man-made slopes and cliffs, 15 ft. (4.5 m) or more high; formed dominantly of sandstone, limestone, sandy shale, mudstone and claystone. Interbedded mudstone, claystone and shale weather rapidly leaving sandstone and limestone rock faces unsupported.

SOIL AND ROCK SUSCEPTIBLE TO LANDSLIDING Soil and rock similar to that involved in landslides elsewhere in map area; primarily areas underlain by claystone, mudstone and shale associated with other rock types. Rock weathers rapidly on exposure forming clayey soil highly susceptible to sliding. Includes coves (U-shaped, shallow valleys) containing thick layers of clayey . soil that are very susceptible to sliding where excavation breaks continuity of slope and where overloaded by artificial fill.

AREAS LEAST PRONE TO LANDSLIDES Map areas in which no patterns or symbols are shown; primarily valley floors, ridge tops and broad benches; modification by excavation and fill may

lead to local landslides. The first four digits of the open file number designate the specific 1:250,000 scale map sheet of which this quadrangle is a part. The last two digits designate the position of the quadrangle in a subdivision of the 1:250,000 scale map based

on rows and tiers shown in the diagram to the right. The location of this quadrangle is shown by the black square.

N3745-W8215/7.5 NOTE Information shown is intended as a general guide to ground conditions as of the date of field check. Additional landslides and rockfalls should be anticipated in all map units. The map unit depicts the dominant condition in the area delineated and variations in slope stability may occur at any point in the unit. This map is suitable for general planning purposes and as a supplement to more detailed studies for site selection. The map cannot be used as a substitute for detailed geologic and engineering investigations to establish design and construction criteria of specific sites. Some symbols may not appear on this map because the description is applicable to a

MAN-MADE FEATURES Strip mines (combination of letter symbols indicates complex formed of more than one type of strip mine) bench with high wall furrowed with high wall

multiple furrows and multiple benches

hilltop removed reclaimed by grading

reclaimed by secondary use

regraded in part, high wall remains

Coal refuse banks identified on aerial photographs; not classified in field check

not burnt nor on fire

burnt

burning

sludge

series of maps.

Quarries quarry site

spoil bank, quarry waste

Gravel pits site of gravel pit

Slides in man-made features earth flow in fill

earth flow in strip castings

earth flow in coal refuse JENKINS 1°x2° SHEET

